

**environmental:**

- Eco Solution Q™ is MBDC Cradle-to-Cradle certified
- 100% recyclable through the Shaw Green Edge™ Recycling Program
- contains 25% pre-consumer recycled content
- contributes to LEED point rating system for recycled content, low emitting materials and innovation in design
- Green Label Plus Certified

*After its useful life this product can be recycled again and again by calling 877.502.SHAW (7429)*

<b>construction:</b>	cut pile
<b>fiber type:</b>	100% Eco Solution Q® Premium Branded Nylon
<b>dye method:</b>	dye injection print
<b>gauge:</b>	1/10"
<b>ply:</b>	2
<b>stitches per inch:</b>	12.3
<b>finished pile thickness:</b>	.297
<b>production weight:</b>	40 oz./sq. yd.
<b>density:</b>	4,848 oz./yd.
<b>weight density:</b>	174,528
<b>protective treatments:</b>	stain and bleach resistance
<b>primary backing:</b>	polypropylene
<b>secondary backing:</b>	classicbac™
<b>application:</b>	heavy traffic
<b>wearability:</b>	20 year wear warranty

Specifications are subject to normal manufacturing tolerances.

**Flooring Radiant Panel (ASTM E-648):**

Class I

**Smoke Density (ASTM E-662):**

Less than 450

**Electrostatic Propensity:**

Less than 3.5 KV

**Methenamine Pill Test (DOC FF-1-70)**

Passes

**ADA Compliance:**

This product meets the Guidelines as Set Forth in the Americans with Disabilities Act for Minimum Static Coefficient of Friction for 0.5 for Accessible Routes.