


stria 36



environmental:

- Eco Solution Q™ is MBDC Cradle-to-Cradle certified
- 100% recyclable through the Shaw Green Edge™ Recycling Program
- contains 25% pre-consumer recycled content
- contributes to LEED point rating system for recycled content, low emitting materials and innovation in design
- Green Label Plus Certified

After its useful life this product can be recycled again and again by calling 877.502.SHAW(7429)

construction:	textured cut/loop
fiber type:	100% Eco Solution Q® Premium Branded Nylon
dye method:	dye injection print
gauge:	1/10"
ply:	2
stitches per inch:	12.8
finished pile thickness:	.235
production weight:	36 oz./sq. yd.
density:	5514 oz./yd.
weight density:	198,504
protective treatments:	stain and bleach resistance
primary backing:	polypropylene
secondary backing:	classicbac™
application:	heavy traffic
wearability:	20 year wear warranty

Specifications are subject to normal manufacturing tolerances.

Flooring Radiant Panel (ASTM E-648):
Class I

Smoke Density (ASTM E-662):
Less than 450

Electrostatic Propensity:
Less than 3.5 KV

Methenamine Pill Test (DOC FF-1-70)
Passes

ADA Compliance:

This product meets the Guidelines as Set Forth in the Americans with Disabilities Act for Minimum Static Coefficient of Friction for 0.5 for Accessible Routes.