stria 42





- Eco Solution Q™ is MBDC Cradle-to-Cradle certified

- 100% recyclable through the Shaw Green Edge™ Recycling Program

environmental: - contains 25% pre-consumer recycled content

- contributes to LEED point rating system for recycled content,

low emitting materials and innovation in design

- Green Label Plus Certified

After its useful life this product can be recycled again and again by calling 877.502.SHAW(7429)

construction: textured cut/loop

fiber type: 100% Eco Solution Q® Premium Branded Nylon

dye method: dye injection print

gauge: 1/10"

ply: 2 stitches per inch: 13.6

finished pile thickness: .261

production weight: 42 oz./sq. yd. density: 5793 oz./yd. weight density: 208,548

protective treatments: stain and bleach resistance

primary backing: polypropylene
secondary backing: classicbac™
application: heavy traffic

wearability: 20 year wear warranty

Specifications are subject to normal manufacturing tolerances.

Flooring Radiant Panel (ASTM E-648): Smoke Density (ASTM E-662):

Class I Less than 450

Electrostatic Propensity: Methenamine Pill Test (DOC FF-1-70)

Less than 3.5 KV Passes

ADA Compliance:

This product meets the Guidelines as Set Forth in the Americans with Disabilities Act for Minimum Static Coefficient of Friction for 0.5 for Accessible Routes.



