

Metropolis Specifications			
Manufacturing Process	Needlefelt	Luxury Class	LC2
Surface Aspect	Velour	Colour Fastness to Light	≥ 5
Pile Yarn Composition	100% ASOTA Polypropylene Fibres	Colour Fastness to Water	≥ 4
Overall Use Class	Areas With Heavy Use	Colour Fastness to Soiling	≥ 3
Width	200 cm (6'-7")	Colour Fastness to Rubbing, Dry / Wet	≥ 4
Pile Weight	1770 g/m²	Electrostatic Charging	<2kV
Total Weight	2760 g/m² (+/-10%)		
Pile Height	6 mm		
Total Height	12.5 mm (+/-10%)	Slip Resistance	>0.3 Machine Direction >0.3 Cross Direction
Flammability	Efl		
Backing	Eco-Di-Back Natural-Synthetic Composite Rubber		

These products meet C.G.S.B. standards for flammability. (Methenamine pile Test)

All Vifloor Canada Ltd. products meet ISO 9002 Certification.

All Vifloor Canada Ltd. products contribute towards LEED certification.

Product of Netherlands (E.U.)



Toll: 1-877-521-9014

www.vifloor.com

10 Queen Elizabeth Vld.

Unit 1, Toronto, ON

M8Z 1L8