

EcoLogix® Tile

backing system:	EcoLogix®
features + benefits:	performance precoat, fiberglass reinforced thermoplastic layer laminated with a fiber matrix secondary containing 100% post consumer material
backing process:	6-step process <ol style="list-style-type: none">1. High performance precoat for maximum tuft bind and moisture resistance.2. Thermoplastic laminate for superior delamination strength.3. Fiberglass reinforcement for unmatched stability.4. Thermoplastic laminate.5. Attached post consumer recycled fiber matrix pad for comfort under foot.6. Die-cut into carpet tile.
primary:	synthetic
stabilizer:	fiberglass
weight:	85 oz/sy
secondary thickness:	0.185 inch
dimensions:	24" x 24"; additional sizes available
pad density:	8.5 – 9.5 lbs. per cubic foot
testing:	Radiant Panel Fire Class I (based on pile construction) NBS Smoke < 450 (based on pile construction) Passes CRI Green Label Plus Requirements Moisture Barrier - 24 hour British Spill
installation:	full spread Shaw Sureset 5000 and 5100, antimicrobial Shaw 5036 pressure sensitive adhesives EcoLogix ES: Shaw's environmental self-adhesive system (custom option)
warranty:	Lifetime Commerical Limited Warranty

